

Dist	COUNTY	ROUTE	POST MILES TOTAL PROJECT	SHEET No.	TOTAL SHEETS
08	Riv,SBd	10,91,215	Var		

REGISTERED CIVIL ENGINEER DATE

PLANS APPROVAL DATE

THE STATE OF CALIFORNIA OR ITS OFFICERS OR AGENTS SHALL NOT BE RESPONSIBLE FOR THE ACCURACY OR COMPLETENESS OF SCANNED COPIES OF THIS PLAN SHEET.

RELEASED 3/16/2012

STATE OF CALIFORNIA - DEPARTMENT OF TRANSPORTATION DESIGN

COLUMN TITLES:
FT=3, TX=8.75,
WT=2, LV=60,
Upper Case
except for Std
abbreviations

If the Locations of Construction table is on a Locations of Construction sheet instead of the title sheet, the cell AC=LOC2 may be used. At a minimum, the table should include location number, county, route and post mile. The post mile column may indicate a "spot" location or a "to/from" location. The cell includes optional columns for description and direction.

TABLE TITLE:
FT=43, TX=12, WT=0, LV=60, CO=0
See Title Sheet Example "J" for size of text when table is placed on the Title Sheet.
Table Title is to be placed outside and above the table.

LOCATIONS OF CONSTRUCTION

Loc No.Ⓢ	COUNTY	ROUTE	PM	Loc No.Ⓢ	COUNTY	ROUTE	PM	Loc No.Ⓢ	COUNTY	ROUTE	PM	Loc No.Ⓢ	COUNTY	ROUTE	PM
1	SBd	10	9.7	34	SBd	10	28.4	67	Riv	10	6.2	100	SBd	215	1.3
2	SBd	10	10.2	35	SBd	10	29.1	68	Riv	10	6.6	101	SBd	215	1.9
3	SBd	10	12.1	36	SBd	10	29.5	69	Riv	10	6.8	102	SBd	215	2.7
4	SBd	10	12.6	37	SBd	10	29.9	70	Riv	91	0.9	103	SBd	215	3.5
5	SBd	10	13.0	38	SBd	10	30.3	71	Riv	91	3.5	104	SBd	215	4.6
6	SBd	10	13.4	39	SBd	10	30.7	72	Riv	91	3.8	105	SBd	215	5.1
7	SBd	10	13.8	40	SBd	10	30.9	73	Riv	91	4.2	106	SBd	215	5.6
8	SBd	10	14.4	41	SBd	10	31.1	74	Riv	91	5.2	107	SBd	215	6.6
9	SBd	10	15.1	42	SBd	10	31.7	75	Riv	91	5.5	108	SBd	215	7.1
10	SBd	10	15.3	43	SBd	10	32.2	76	Riv	215	9.4	109	SBd	215	7.4
11	SBd	10	17.0	44	SBd	10	33.0	77	Riv	215	14.0	110	SBd	215	7.8
12	SBd	10	17.7	45	SBd	10	33.4	78	Riv	215	16.5	111	SBd	215	8.0
13	SBd	10	18.4	46	SBd	10	34.0	79	Riv	215	17.3	112	SBd	215	8.5
14	SBd	10	18.8	47	SBd	10	34.4	80	Riv	215	20.0	113	SBd	215	9.1
15	SBd	10	19.3	48	SBd	10	34.8	81	Riv	215	24.3	114	SBd	215	9.5
16	SBd	10	19.8	49	SBd	10	35.3	82	Riv	215	25.5	115	SBd	215	10.4
17	SBd	10	20.1	50	SBd	10	35.6	83	Riv	215	27.0	116	SBd	215	10.9
18	SBd	10	20.8	51	SBd	10	36.3	84	Riv	215	29.5	117	SBd	215	11.4
19	SBd	10	21.1	52	SBd	10	36.9	85	Riv	215	30.8	118	SBd	215	11.8
20	SBd	10	21.8	53	SBd	10	37.1	86	Riv	215	31.1	119	SBd	215	12.5
21	SBd	10	22.0	54	SBd	10	37.8	87	Riv	215	32.5	120	SBd	215	13.2
22	SBd	10	22.4	55	SBd	10	38.5	88	Riv	215	34.3	121	SBd	215	13.8
23	SBd	10	22.8	56	SBd	10	39.1	89	Riv	215	35.6	122	SBd	215	14.2
24	SBd	10	23.1	57	Riv	10	0.2	90	Riv	215	35.7	123	SBd	215	15.0
25	SBd	10	23.4	58	Riv	10	0.7	91	Riv	215	35.8	124	SBd	215	15.7
26	SBd	10	23.9	59	Riv	10	1.0	92	Riv	215	36.4	125	SBd	215	16.4
27	SBd	10	24.4	60	Riv	10	2.0	93	Riv	215	36.5	126	SBd	215	17.1
28	SBd	10	25.3	61	Riv	10	R3.0	94	Riv	215	37.2	127	SBd	215	17.3
29	SBd	10	26.1	62	Riv	10	3.1	95	Riv	215	37.5				
30	SBd	10	26.5	63	Riv	10	R3.9	96	Riv	215	38.4				
31	SBd	10	26.8	64	Riv	10	R4.6	97	Riv	215	43.9				
32	SBd	10	27.6	65	Riv	10	R5.4	98	SBd	215	0.1				
33	SBd	10	27.9	66	Riv	10	5.6	99	SBd	215	0.5				

ALL TEXT IN TABLE:
FT=3, TX=7,
WT=1, LV=60, CO=0
Upper Case except for
standard abbreviations

LINE WIDTHS FOR THE TABLE:
Horizontal line separating heading;
WT=1, LV=60, CO=0
Horizontal lines separating rows;
WT=0, LV=60, CO=0
Vertical lines separating columns;
WT=1, LV=60, CO=0
Exterior border;
WT=2, LV=60, CO=0

SPACING BETWEEN ROWS
(for single row of text):
Use 14 feet between rows
so half the height of the
text is above and below
the text for each row.

LOCATIONS OF CONSTRUCTION

LOCATIONS OF CONSTRUCTION SHEET, FOR TITLE SHEET EXAMPLE "K"

LC-1