California Test **109**

AC, PCC, Rubber & Other Batch Operations

Report Number 23-16 | calib date 06/29/2016 | district 01 | 109 by L Lee | plant controller SELTEC 920I

plant type Batch | plant owner Mercer Fraser | plant location Plant "A" River Walk Dr. Fortuna CA

scale acceptable to 6000 | useable scale capacity 10000 | largest noted error, for this scale 1 Grad

scale number 1 | material type aggregate | graduation size 10

step number	applied test weight	applied build-up weight	total applied weight	adjustment from last step	adjusted total weight	indicated weight	actual error	error in grads	USEABILITY	remarks
1	1000	0	1000	always zero for 1st step	1000	1000	0.0	0.0	Acceptable	
2	2000	0	2000	0	2000	2000	0.0	0.0	Acceptable	
3	3000	0	3000	0	3000	3000	0.0	0.0	Acceptable	
4	4000	0	4000	0	4000	4000	0.0	0.0	Acceptable	
5	5000	0	5000	0	5000	5000	0.0	0.0	Acceptable	
6	6000	0	6000	0	6000	6000	0.0	0.0	Acceptable	

scale acceptable to 400 | useable scale capacity 500 | largest noted error, for this scale 1 Grad

scale number 2 | material type asphalt | graduation size 1

step number	applied test weight	applied build-up weight	total applied weight	adjustment from last step	adjusted total weight	indicated weight	actual error	error in grads	USEABILITY	remarks
1	100	0	100	always zero for 1st step	100	100	0	0	Acceptable	
2	200	0	200	0	200	200	0	0	Acceptable	
3	300	0	300	0	300	300	0	0	Acceptable	
4	400	0	400	0	400	400	0	0	Acceptable	
		0	0	0	0		0	0	Acceptable	

scale acceptable to 500 | useable scale capacity 500 | largest noted error, for this scale

scale number 3 | material type LAS | graduation size 1

step number	applied test weight	applied build-up weight	total applied weight	adjustment from last step	adjusted total weight	indicated weight	actual error	error in grads	USEABILITY	remarks
1	50.27		50.27	always zero for 1st step	50.27	50.2	-.07	-.07	Acceptable	17:00 min 0.1% 120 lbph
2	50.17		50.17	0	50.17	50.2	.03	.03	Acceptable	17:36 min 0.1% 120 lbph

scale acceptable to | useable scale capacity | largest noted error, for this scale

scale number | material type | graduation size

step number	applied test weight	applied build-up weight	total applied weight	adjustment from last step	adjusted total weight	indicated weight	actual error	error in grads	USEABILITY	remarks
				always zero for 1st step						

Test Notes

LAS only runs at 120 lbph SPAN 5.1420
Plant Certified for State Use
Interlocks O.K.
Printer O.K.