

## PREQUALIFIED LIST OF COUPLERS ON REINFORCING STEEL

Type of Splice	Splice Company	Coupler Model	Service Splice Qualification (Bar Sizes)	Ultimate Splice Qualification (Bar Sizes)
<b><i>Mechanical Couplers on ASTM A 706 Reinforcing Steel</i></b>				
Sleeve-Swaged (Deformation Dependent)	BarSplice	BPI-GRIP™ (BarGrip®)	#3 through #18	
	BarSplice	BPI-GRIP™ (BarGrip®) XL	#5 through #18	#5 through #18
	BarSplice	Taper Threaded Grip-Twist®	#3 through #18; #11 to #18 transition; #11 to #14 transition; and #10 to #18 transition	#3 through #18; #11 to #18 transition; #11 to #14 transition; and #10 to #18 transition
	BarSplice	Grip Twist Position System	#5 through #18	-
	Dextra America, Inc.	Griptec®	#4 through #18	
Sleeve-Forged	Dayton/Richmond (formerly Richmond Screw Anchor Co.)	DB/DI	#4 through #11	#4 through #11
	Dayton/Richmond (formerly Richmond Screw Anchor Co.)	US/MC	#4 through #18	#4 through #18
	Dextra America, Inc.	Bartec, Position Splices Type A, B, and C.	#4 through #18	#4 through #18
Sleeve-Lock Shear Bolts	Dayton Superior (formerly Bar-Lock)	Bar-Lock S/CA Series (formerly S-series)	#4 through #18	
	Dayton Superior (formerly Bar-Lock)	Bar-Lock S/CA Series (formerly S-series)	#5 to #6 transition	
	BarSplice	ZAP Screwlok® Type 2 Series (Standard)	#4 through #11	
	BarSplice	ZAP Screwlok® Transition Coupler	#7/#5	
	Dayton Superior (formerly Bar-Lock)	Bar-Lock L Series	#3 through #14; and green epoxy-coated	
	ERICO Inc.	Lenton Lock (B1 Series)	#4 through #11	#4 through #11
	ERICO Inc.	Lenton Lock (S1 Series) Foreign Made	#4 through #18	

Notes:

1. If there is a discrepancy between this list and the prequalification letter issued by the California Department of Transportation ("Caltrans") to the splice company, the approval letter and any conditions therein control.
2. The splice company shall inform Caltrans if any of the following occur: the design of the coupler changes, the material used in the coupler changes, changes to the manufacturing process including location changes of manufacturing plants. Caltrans may revoke the prequalification of a mechanical coupler, and remove it from this list for any of these reasons or if the splice company engages in fraud or misrepresentation in order to comply with the quality control and quality assurance requirements in section 52 of the Standard Specifications.
3. Caltrans takes no position respecting the validity of any intellectual property rights asserted in connection with any coupler on this list. Users of this list are solely responsible for determining the validity of any such intellectual property rights.
4. All mechanical couplers are on plain black bar unless otherwise stated. Couplers on epoxy-coated bars require a plastic shrink sleeve cover.
5. Service and ultimate splices are defined in section 52 of the Standard Specifications.
6. This table was prepared to provide a reference source for rebar splicing systems currently prequalified for use by Caltrans. Caltrans assumes no liability or responsibility for the accuracy or validity of this information if used by other entities.
7. If you have any questions about this list, please contact the appropriate Structural Materials Representative at <http://www.dot.ca.gov/hq/esc/Translab/smforms/StructuralMaterialsRepresentatives.pdf>.

## PREQUALIFIED LIST OF COUPLERS ON REINFORCING STEEL

Type of Splice	Splice Company	Coupler Model	Service Splice Qualification (Bar Sizes)	Ultimate Splice Qualification (Bar Sizes)
<b><i>Mechanical Couplers on ASTM A 706 Reinforcing Steel</i></b>				
Sleeve –Tapered Thread	Erico	Lenton <sup>®</sup> Standard (A2)	#3 through #18	
	Erico	Lenton <sup>®</sup> Transition (A2)	#5/#4 through #18/#14	
	Erico	Lenton <sup>®</sup> Position (P8)	#6 through #18	
	Erico	Lenton <sup>®</sup> Position (P9)	#6 through #18	
	Erico	Lenton <sup>®</sup> Formsaver	#3 through #11	
	Erico	Lenton <sup>®</sup> Interlock <sup>™</sup> Rebar Splice System	#8	#8
	Erico	Lenton <sup>®</sup> Plus Position Coupler (P14L)	#8 through #14	#8 through #14
	Erico	Lenton <sup>®</sup> Plus Standard Coupler (A12)	#5 through #14	#5 through #14
	Fox-Howlett	Standard No-Slip Couplers	#6 through #18	
	Fox-Howlett	Position No-Slip Couplers	#6 through #18	
	Headed Reinforcement Corp.	HRC 410/420 Standard Coupler	#8 through #18	#8 through #18
	Headed Reinforcement Corp.	HRC 410/490 Position Coupler	#8 through #18	#8 through #18
	Dayton Superior	Taper Lock D-310 Standard Coupler	#6 through #14	
	Dayton Superior	Taper Lock D-330 Positional Coupler	#6 through #14	
Dayton Superior	Taper Lock D-340 Flange Coupler	#6 through #14		
Sleeve-Filler Metal	Erico	Cadweld	#18	
Sleeve-Filler Grout Coupler	Splice Sleeve North America	NMB	#4 through #18	

Notes:

1. If there is a discrepancy between this list and the prequalification letter issued by the California Department of Transportation ("Caltrans") to the splice company, the approval letter and any conditions therein control.
2. The splice company shall inform Caltrans if any of the following occur: the design of the coupler changes, the material used in the coupler changes, changes to the manufacturing process including location changes of manufacturing plants. Caltrans may revoke the prequalification of a mechanical coupler, and remove it from this list for any of these reasons or if the splice company engages in fraud or misrepresentation in order to comply with the quality control and quality assurance requirements in section 52 of the Standard Specifications.
3. Caltrans takes no position respecting the validity of any intellectual property rights asserted in connection with any coupler on this list. Users of this list are solely responsible for determining the validity of any such intellectual property rights.
4. All mechanical couplers are on plain black bar unless otherwise stated. Couplers on epoxy-coated bars require a plastic shrink sleeve cover.
5. Service and ultimate splices are defined in section 52 of the Standard Specifications.
6. This table was prepared to provide a reference source for rebar splicing systems currently prequalified for use by Caltrans. Caltrans assumes no liability or responsibility for the accuracy or validity of this information if used by other entities.
7. If you have any questions about this list, please contact the appropriate Structural Materials Representative at <http://www.dot.ca.gov/hq/esc/Translab/smforms/StructuralMaterialsRepresentatives.pdf>.

## PREQUALIFIED LIST OF COUPLERS ON REINFORCING STEEL

Type of Splice	Splice Company	Coupler Model	Service Splice Qualification (Bar Sizes)	Ultimate Splice Qualification (Bar Sizes)
<b><i>Mechanical Couplers on ASTM A 706 Reinforcing Steel</i></b>				
Upset Bar Ends-Dowel Bars Included	Dayton/Richmond	US/MC Forged	#6 through #11	#7 through #11
Two Piece, Weld-On Coupler	Headed Reinforcement Corp.	Xtender® XT 553 Anchor Coupler	#7 and #8	#7 and #8
Two Piece Sleeve/Forged Ends	Headed Reinforcement Corp.	Xtender® 507/571 Coupler	#7	#7
	Headed Reinforcement Corp.	Xtender® 507/571 Position Coupler	#11	#11
	Headed Reinforcement Corp.	Xtender® 500/510 Standard Coupler	#4 through #14	#4 through #14
	Headed Reinforcement Corp.	Xtender® 500/510 Transition Coupler	#4 through #14	#4 through #14
	Headed Reinforcement Corp.	Xtender® 500/510 Transition Nut Coupler	#5 through #11	#5 through #11
	Headed Reinforcement Corp.	Xtender® 500/510 Transition Nut Coupler	#11 to #14	#11 to #14
	Headed Reinforcement Corp.	Xtender® 500/520 Form Protector	#4 through #14	#4 through #14
Wedge-Thru Sleeve (Mechanical Lap Splice)	OCM, Inc. (formerly Splice Sleeve North America)	O-S Splice Clip (one clip per splice)	#4 through #6	
	Erico	Quick-wedge Mechanical Lap Coupling Device (Single Clip)	#4 through #6	
	Erico	Quick-wedge Mechanical Lap Coupling Device (two clips per splice)	#4 through #6	
Side-by-Side	BarSplice	ZAP Screwlok® Double Barrel Transition Coupler	#4/#3 through #6/#5	

Notes:

1. If there is a discrepancy between this list and the prequalification letter issued by the California Department of Transportation ("Caltrans") to the splice company, the approval letter and any conditions therein control.
2. The splice company shall inform Caltrans if any of the following occur: the design of the coupler changes, the material used in the coupler changes, changes to the manufacturing process including location changes of manufacturing plants. Caltrans may revoke the prequalification of a mechanical coupler, and remove it from this list for any of these reasons or if the splice company engages in fraud or misrepresentation in order to comply with the quality control and quality assurance requirements in section 52 of the Standard Specifications.
3. Caltrans takes no position respecting the validity of any intellectual property rights asserted in connection with any coupler on this list. Users of this list are solely responsible for determining the validity of any such intellectual property rights.
4. All mechanical couplers are on plain black bar unless otherwise stated. Couplers on epoxy-coated bars require a plastic shrink sleeve cover.
5. Service and ultimate splices are defined in section 52 of the Standard Specifications.
6. This table was prepared to provide a reference source for rebar splicing systems currently prequalified for use by Caltrans. Caltrans assumes no liability or responsibility for the accuracy or validity of this information if used by other entities.
7. If you have any questions about this list, please contact the appropriate Structural Materials Representative at <http://www.dot.ca.gov/hq/esc/Translab/smforms/StructuralMaterialsRepresentatives.pdf>.

## PREQUALIFIED LIST OF COUPLERS ON REINFORCING STEEL

Type of Splice	Splice Company	Coupler Model	Service Splice Qualification (Bar Sizes)	Ultimate Splice Qualification (Bar Sizes)
<b><i>Mechanical Couplers on ASTM A 706 Reinforcing Steel</i></b>				
(Mechanical Lap Splice)	BarSplice	ZAP Screwlok® Double Barrel Standard Coupler	#4 through #6	

Type of Splice	Splice Company	Coupler Model	Service Splice Qualification (Bar Sizes)	Ultimate Splice Qualification (Bar Sizes)
<b><i>Mechanical Couplers on ASTM A 706 Reinforcing Steel Hoops</i></b>				
Sleeve-Swaged	BarSplice	BPI-GRIP™ (BarGrip®)	#5 through #8, and #14	
Two Piece Sleeve/ Forged Ends	Headed Reinforcement Corp.	Xtender® 500/510	#5 through #11	#8, #9 and #11
	Headed Reinforcement Corp.	Xtender® 500/515 adjustable tension hoop coupler	#8	
	Headed Reinforcement Corp.	HRC 500/571 adjustable tension hoop coupler	#8	

Type of Splice	Splice Company	Coupler Model	Service Splice Qualification (Bar Sizes)	Ultimate Splice Qualification (Bar Sizes)
<b><i>Mechanical Couplers on ASTM A 615, Grade 75 Reinforcing Steel</i></b>				
Sleeve-Threaded Bar	Dywidag Systems International	A 615, grade 75 reinforcement bar splice	#11, #18 and #20	
	Williams Form Engineering	A615, grade 75 reinforcement bar splice	#14 and #18	

Notes:

1. If there is a discrepancy between this list and the prequalification letter issued by the California Department of Transportation ("Caltrans") to the splice company, the approval letter and any conditions therein control.
2. The splice company shall inform Caltrans if any of the following occur: the design of the coupler changes, the material used in the coupler changes, changes to the manufacturing process including location changes of manufacturing plants. Caltrans may revoke the prequalification of a mechanical coupler, and remove it from this list for any of these reasons or if the splice company engages in fraud or misrepresentation in order to comply with the quality control and quality assurance requirements in section 52 of the Standard Specifications.
3. Caltrans takes no position respecting the validity of any intellectual property rights asserted in connection with any coupler on this list. Users of this list are solely responsible for determining the validity of any such intellectual property rights.
4. All mechanical couplers are on plain black bar unless otherwise stated. Couplers on epoxy-coated bars require a plastic shrink sleeve cover.
5. Service and ultimate splices are defined in section 52 of the Standard Specifications.
6. This table was prepared to provide a reference source for rebar splicing systems currently prequalified for use by Caltrans. Caltrans assumes no liability or responsibility for the accuracy or validity of this information if used by other entities.
7. If you have any questions about this list, please contact the appropriate Structural Materials Representative at <http://www.dot.ca.gov/hq/esc/Translab/smforms/StructuralMaterialsRepresentatives.pdf>.

## PREQUALIFIED LIST OF COUPLERS ON REINFORCING STEEL

Type of Splice	Splice Company	Coupler Model	Service Splice Qualification (Bar Sizes)	Ultimate Splice Qualification (Bar Sizes)
<b><i>Mechanical Couplers on ASTM A 722, Grade 150 Bars</i></b>				
Sleeve-Threaded Bar	Williams Form Engineering	A 722 Splice	2.5-inch	

Notes:

1. If there is a discrepancy between this list and the prequalification letter issued by the California Department of Transportation ("Caltrans") to the splice company, the approval letter and any conditions therein control.
2. The splice company shall inform Caltrans if any of the following occur: the design of the coupler changes, the material used in the coupler changes, changes to the manufacturing process including location changes of manufacturing plants. Caltrans may revoke the prequalification of a mechanical coupler, and remove it from this list for any of these reasons or if the splice company engages in fraud or misrepresentation in order to comply with the quality control and quality assurance requirements in section 52 of the Standard Specifications.
3. Caltrans takes no position respecting the validity of any intellectual property rights asserted in connection with any coupler on this list. Users of this list are solely responsible for determining the validity of any such intellectual property rights.
4. All mechanical couplers are on plain black bar unless otherwise stated. Couplers on epoxy-coated bars require a plastic shrink sleeve cover.
5. Service and ultimate splices are defined in section 52 of the Standard Specifications.
6. This table was prepared to provide a reference source for rebar splicing systems currently prequalified for use by Caltrans. Caltrans assumes no liability or responsibility for the accuracy or validity of this information if used by other entities.
7. If you have any questions about this list, please contact the appropriate Structural Materials Representative at <http://www.dot.ca.gov/hq/esc/Translab/smforms/StructuralMaterialsRepresentatives.pdf>.