

DEPARTMENT OF TRANSPORTATION

DIVISION OF ENGINEERING SERVICES

OFFICE ENGINEER

1727 30th Street MS-43

P.O. BOX 168041

SACRAMENTO, CA 95816-8041

FAX (916) 227-6214

www.dot.ca.gov/hq/esc/oe

*Serious Drought.
Help save water!*

November 7, 2014

06-Fre-5-48.8/53.0

06-0Q2704

Project ID 0613000050

ACNHPI-005-5(144)E

Addendum No. 3

Dear Contractor:

This addendum is being issued to the contract for CONSTRUCTION ON STATE HIGHWAY IN FRESNO COUNTY ABOUT 38 MILES SOUTH OF SANTA NELLA FROM 0.1 MILE SOUTH OF PANOCHÉ ROAD OVERCROSSING TO 0.2 MILE NORTH OF RUSSELL AVENUE OVERCROSSING.

Submit bids for this work with the understanding and full consideration of this addendum. The revisions declared in this addendum are an essential part of the contract.

Bids for this work will be opened on Thursday, November 13, 2014.

This addendum is being issued to revise the project plans, the *Notice to Bidders and Special Provisions*, and the *Bid* book.

Project plan sheets 67 and 68 are replaced and attached for substitution for the like-numbered sheets.

In the Special Provisions, Section 19, "Earthwork," the following paragraph is added before the first paragraph:

"Replace the second, third and fourth paragraphs of section 19-2.03B with:

Dispose of surplus material. Ensure enough material is available to complete the embankments before disposing of it."

In the Special Provisions, section 36-2 is added as attached.

Addendum No. 3
Page 2
November 7, 2014

06-Fre-5-48.8/53.0
06-0Q2704
Project ID 0613000050
ACNHPI-005-5(144)E

In the *Bid* book, in the "Bid Item List," Item 25 is replaced.

To *Bid* book holders:

Inquiries or questions in regard to this addendum must be communicated as a bidder inquiry and must be made as noted in the *Notice to Bidders* section of the *Notice to Bidders and Special Provisions*.

Submit the *Bid* book as described in the *Electronic Bidding Guide* at the Bidders' Exchange website.

http://www.dot.ca.gov/hq/esc/oe/electronic_bidding/electronic_bidding.html

Inform subcontractors and suppliers as necessary.

This addendum, EBS addendum file and the attachments are available for the Contractors' download on the Web site:

http://www.dot.ca.gov/hq/esc/oe/project_ads_addenda/06/06-0Q2704

If you are not a *Bid* book holder, but request a book to bid on this project, you must comply with the requirements of this letter before submitting your bid.

Sincerely,



SHARRI BENDER EHLERT
District Director
District 6 Central Region

Attachments

Replace "Reserved" in the RSS for section 36-2 with:

36-2.01 GENERAL

36-2.01A Summary

Section 36-2 includes specifications for placing base bond breaker.

36-2.01B Definitions

Not Used

36-2.01C Submittals

Submit a certificate of compliance for each lot of base bond breaker material delivered.

36-2.01D Quality Control and Assurance

Not Used

36-2.02 MATERIALS

Base bond breaker must comply with the specifications shown in the following table:

Base bond breaker no.	Specification
1	PG asphalt binder, Grade PG 64-10
2	Curing compound no. 3
3	White opaque polyethylene film under ASTM C 171 except the minimum thickness must be 6 mils
4	White curing paper under ASTM C 171
5	Geosynthetic bond breaker

Use base bond breaker no. 1, 2, or 5 on concrete base and LCB.

Use base bond breaker no. 3, 4, or 5 on lean concrete base rapid setting, CTPB, and rapid strength concrete base.

36-2.03 CONSTRUCTION

36-2.03A General

Before placing base bond breaker, remove foreign and loose materials from the base.

Do not place base bond breaker until the base has cured. Allow base bond breaker nos. 1 and 2 to cure before paving.

Within 72 hours of placing base bond breaker, pave over the base bond breaker.

36-2.03B Placing Base Bond Breaker

Place base bond breaker no. 1 in one application at a uniform rate from 0.09 to 0.15 gal/sq yd over the entire base surface area. Allow at least 4 hours for curing.

Comply with section 90-1.03B(3)(c) for mixing base bond breaker no. 2. Place base bond breaker no. 2 in one or more applications to achieve a coverage rate of at least 0.12 gal/sq yd over the entire base surface area. Allow at least 4 hours for curing.

CONTRACT NO. 06-0Q2704
ADDED PER ADDENDUM NO. 3 DATED NOVEMBER 7, 2014

BID ITEM LIST**06-0Q2704**

Item No.	Item Code	Item Description	Unit of Measure	Estimated Quantity	Unit Price	Item Total
21	150771	REMOVE ASPHALT CONCRETE DIKE	LF	9,180		
22	150814	REMOVE DOWNDRAIN (EA)	EA	2		
23	150854	REMOVE CONCRETE PAVEMENT (CY)	CY	800		
24	150859	REMOVE ASPHALT CONCRETE OVERSIDE DRAIN	EA	11		
25	153103	COLD PLANE ASPHALT CONCRETE PAVEMENT	SQYD	276,000		
26	160102	CLEARING AND GRUBBING (LS)	LS	LUMP SUM	LUMP SUM	
27	190101	ROADWAY EXCAVATION	CY	15,300		
28	190185	SHOULDER BACKING	TON	4,580		
29	250201	CLASS 2 AGGREGATE SUBBASE	CY	9,220		
30	260203	CLASS 2 AGGREGATE BASE (CY)	CY	4,830		
31	390132	HOT MIX ASPHALT (TYPE A)	TON	69,100		
32	390137	RUBBERIZED HOT MIX ASPHALT (GAP GRADED)	TON	22,200		
33	393004	GEOSYNTHETIC PAVEMENT INTERLAYER (PAVING FABRIC)	SQYD	31,900		
34	394053	SHOULDER RUMBLE STRIP (HMA,GROUND-IN INDENTATIONS)	STA	720		
35	394060	DATA CORE	LS	LUMP SUM	LUMP SUM	
36	394073	PLACE HOT MIX ASPHALT DIKE (TYPE A)	LF	360		
37	394076	PLACE HOT MIX ASPHALT DIKE (TYPE E)	LF	8,820		
38	394090	PLACE HOT MIX ASPHALT (MISCELLANEOUS AREA)	SQYD	430		
39	397005	TACK COAT	TON	59		
40	400050	CONTINUOUSLY REINFORCED CONCRETE PAVEMENT	CY	15,000		