


Dist	COUNTY	ROUTE	POST MILES TOTAL PROJECT	SHEET TOTAL SHEETS

REGISTERED CIVIL ENGINEER
 Effthymios Delis
 No. C51434
 Exp. 6-30-17
 CIVIL
 STATE OF CALIFORNIA

October 30, 2015
 PLANS APPROVAL DATE


THE STATE OF CALIFORNIA OR ITS OFFICERS OR AGENTS SHALL NOT BE RESPONSIBLE FOR THE ACCURACY OR COMPLETENESS OF SCANNED COPIES OF THIS PLAN SHEET.

TO ACCOMPANY PLANS DATED _____




NOTE:
 Type "B" seal shown. Type "A" seals to conform to the general path of seal shown, cuts for bending not required. Bend type "A" seals 3' up into curb or barrier rail on only the low end of the seal.

CONCRETE BARRIER AND SIDEWALK




CONCRETE BARRIER




FORMING DETAIL SAWCUT DETAIL

NOTE:
 The Contractor shall verify all controlling field dimensions before ordering or fabricating any material.

JOINT SEALS DETAILS




PLAN OF JOINT (SKEW ≤ 20°)



PLAN OF JOINT (SKEW > 20°)

Min @ RADIUS TO BE 4 TIMES UNCOMPRESSED WIDTH OF SEAL OR AS RECOMMENDED BY THE MANUFACTURER, WHICHEVER IS GREATER

IN LIEU OF SAW CUTTING, THIS AREA MAY BE BLOCKED OUT AND RECONSTRUCTED TO MATCH SAW CUTTING ON BOTH SIDES.




DETAIL A

- NOTES:**
- Make smooth cuts from the bottom of seal to 1 1/2" clear of top leaving at least one complete cell between the top of the cut and top of the seal. When necessary cut back of seal to clear conduit and round openings.
 - Opening in barrier to match width of sawn deck joint.
 - Sawcut groove widths shall be as ordered by the Engineer.
 - Depth of sawcut: Type A - Depth to be 2" minimum. Type B - Depth to be equal to or greater than the depth of seal measured along the contact surface, when compressed to minimum width position (W₂) plus dimensions shown.
 - MR (movement rating) as shown on other plan sheets.
 - Other depths must be approved by the Engineer.
 - A sidewalk joint shall be covered by an expansion joint armor.


DIMENSIONS "a" OF JOINT REQUIRED

MOVEMENT RATING (MR) (5)	BRIDGE TYPE	"a" DIMENSION DECK CONCRETE PLACED		
		WINTER	FALL-SPRING	SUMMER
2"	ALL EXCEPT CIP/PS	1 1/2"	1 1/4"	3/4"
	CIP/PS	1 1/4"	1"	1/2"
1 1/2"	ALL EXCEPT CIP/PS	1 1/4"	1"	1/2"
	CIP/PS	1"	3/4"	1/2"
1"	ALL EXCEPT CIP/PS	1"	3/4"	1/2"
	CIP/PS	3/4"	1/2"	1/2"
1/2"	ALL EXCEPT CIP/PS	3/4"	3/4"	1/2"
	CIP/PS	1/2"	1/2"	1/2"




TYPE A SEAL

Movement rating : Silicone = 1" Max




TYPE A1 SEAL

Longitudinal joints only



TYPE B JOINT SEAL IN MINIMUM WIDTH POSITION (W₂)



TYPE B SEAL

Movement Rating ≤ 2"

STATE OF CALIFORNIA
 DEPARTMENT OF TRANSPORTATION
JOINT SEALS
(MAXIMUM MOVEMENT RATING = 2")

NO SCALE
 RSP B6-21 DATED OCTOBER 30, 2015 SUPERSEDES STANDARD PLAN B6-21 DATED MAY 20, 2011 - PAGE 283 OF THE STANDARD PLANS BOOK DATED 2010.

REVISED STANDARD PLAN RSP B6-21

2010 REVISED STANDARD PLAN RSP B6-21