


DIST	COUNTY	ROUTE	POST MILES TOTAL PROJECT	SHEET NO.	TOTAL SHEETS


William K. Farnbach
 REGISTERED CIVIL ENGINEER
 No. C49042
 Exp. 9-30-16
 CIVIL
 STATE OF CALIFORNIA

October 30, 2015
 PLANS APPROVAL DATE
 THE STATE OF CALIFORNIA OR ITS OFFICERS OR AGENTS SHALL NOT BE RESPONSIBLE FOR THE ACCURACY OR COMPLETENESS OF SCANNED COPIES OF THIS PLAN SHEET.




CASE 1

Transverse joint more than 2'-0" clear of drainage inlet wall or no transverse joint




CASE 3

Transverse joint within 2'-0" of drainage inlet wall, or matches drainage inlet wall.




CASE 2

Transverse joint intersects drainage inlet, or matches drainage inlet wall.



SECTION A-A

D = Pavement Thickness



DETAIL "A"

ISOLATION JOINT AROUND DRAINAGE INLET

NOTES:

1. Refer to Project Plans for location and Type of drainage inlets.
2. Top of inlet shall be flush with shoulder surface.
3. Extend joint filler material to bottom of Lean Concrete Base. Where Lean Concrete Base is not used as base material, the joint filler material shall only extend to the bottom of the new concrete pavement.
4. For Jointed Plain Concrete Pavement only. For Continuously Reinforced Concrete Pavement, terminate pavement steel reinforcement 2' clear from all outside edges of isolation joint.
5. For Jointed Plain Concrete Pavement only. For Continuously Reinforced Concrete Pavement, see Standard Plan P4.
6. Dowel and tie bars not shown, see Standard Plan P1.

TABLE A

DISTANCE X	BARs REQUIRED
2'-0" TO 1'-6"	2
1'-6" TO 9"	1 @ X/2
9" OR LESS	NONE

STATE OF CALIFORNIA
 DEPARTMENT OF TRANSPORTATION
**CONCRETE PAVEMENT-
 DRAINAGE INLET
 DETAILS No. 1**

NO SCALE