

**CONTRACT CHANGE ORDER NO. 94 SUPPL. NO. 0**  
ROAD 04-SF-80-13.2, 13.9 SHEET 3 OF 13 SHEETS  
FEDERAL NO.(S) \_\_\_\_\_ CONTRACT NO.: 04-0120F4

In Special Provisions Section 10-1.62 "SERVICE PLATFORMS," insert the following after the last paragraph:

Steel grating shall be galvanized in lieu of painting. Galvanizing shall be applied in accordance with the provisions in Section 75-1.05, "Galvanizing," of the Standard Specifications.

Revise the third paragraph of Special Provisions Section 10-1.66 "CLEAN AND PAINT SIGN STRUCTURES," subsection "PAINT GALVANIZED SURFACES," as follows:

The first finish coat shall be applied in 2 applications. The first application shall consist of a spray applied mist application. The second application shall be applied after the mist application has dried to a set to touch condition as determined by the procedure described in Section 7 of ASTM Designation: D1640. The first finish coat color shall ~~match Federal Standard 595B No. 36628~~ conform to Section 10-1.69, "Clean and Paint Structural Steel," of these Special Provisions. The total dry film thickness of both applications of the first finish coat shall be not less than 50 µm.

Revise the fifth paragraph of Special Provisions Section 10-1.66 "CLEAN AND PAINT SIGN STRUCTURES," subsection "PAINT GALVANIZED SURFACES," as follows:

The second finish coat color shall ~~match Federal Standard 595B, No. 26408~~ conform to Section 10-1.69, "Clean and Paint Structural Steel," of these Special Provisions. The total dry film thickness of the applications of the second finish coat shall be not less than 50 µm.

In Special Provisions Section 10-1.75 "MISCELLANEOUS METAL (SERVICE PLATFORMS)," subsection "GENERAL," insert the following after the subsection "Galvanizing":

**Painting**

After galvanizing, Miscellaneous Metal (Service Platforms) shall be painted in conformance with Section 10-1.66, "Clean and Paint Sign Structures," of these Special Provisions. This shall apply to the following items:

- A. Railings
- B. Handrails
- C. Ladders and stairs
- D. Hatchcovers
- E. Hinged covers
- F. Steel rope railing and posts
- G. All anchors, fastenings, hardware, accessories and other supplementary parts necessary to complete the work.



In Special Provisions Section 10-1.78 "BIKEPATH RAILING," insert the following after the last paragraph:

After galvanizing, bikepath railing and posts shall be painted in conformance with Section 10-1.66, "Clean and Paint Sign Structures," of these Special Provisions. Bikepath railing and posts shall be painted prior to installation.